

UT 1153 / 0153 Super-Tack Cleanroom Tape

Description

UltraTape 1153 / 0153 is a high tack cleanroom general purpose and construction tape. It is constructed using a polyethylene backing and rubber adhesive giving it very low outgassing properties and allow it to remove cleanly from most surfaces.

- Clean removal from most surfaces
- Low outgassing
- Easy to tear by hand
- Pen writable

Properties

Backing	Polyethylene
Adhesive	Rubber
Release Liner	NA
Backing Thickness	7 mils
Adhesive Thickness	2.5 mils
Adhesion to Stainless	60 oz/in
Operating Temperature	-20°F to 176°F (-28°C to 80°C)
Tensile Strength	20 lb/in
Length	36 yards
Colors	White (WH), Black (BK), Blue (BL), Blue / White Stripe (BW), Clear (CL), Green (GR), Orange (OR), Red (RE), Yellow (YE)

To achieve ultimate adhesion, the bonding surface should be dry, clean and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

Values should not be used for specification purposes. Each user should make their own test to determine the products suitability for their own intended use and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.

